

COMET Hochdruckpumpen

Premium



Max. 30 °C

P	Q	U	KW	TYP
345	18,0	1.450	15,5	TW 4550S
172	38,0	1.450	12,5	TW 10025S
172	42,5	1.450	13,7	TW 11025S
248	27,0	1.450	16,5	TW 7036 S

R+M Nr.
172 045 500
172 100 250
172 110 250
172 070 360

Reparatursätze



Ventile 6 Stück



Dichtsätze für 3 Kolben



Öldichtungssatz



Plungerrohr-Kit für 3 Kolben

R+M Nr.
172 900 003
172 900 005
172 900 005
172 900 005

R+M Nr.
172 900 027
172 900 020
172 900 020
172 900 028

R+M Nr.
172 900 018
172 900 210
172 900 210
172 900 210

R+M Nr.
172 900 012
172 900 014
172 900 014
172 900 013



Max. 30 °C

P	Q	U	KW	TYP
276	19	1.450	10	RW 5040S

R+M Nr.
172 050 400



Ventile 6 Stück



Dichtsätze für 3 Kolben



Öldichtungssatz



Plungerrohr-Kit für 3 Kolben

R+M Nr.
172 900 002

R+M Nr.
172 900 025

R+M Nr.
172 900 017

R+M Nr.
172 900 010

Standard



Max. 30 °C

P	Q	U	KW	TYP
207	15,0	1.450	5,5	FW2 4030 S
207	18,8	1.450	6,4	FW2 5030 S
207	21,0	1.450	7,1	FW2 5530 S

R+M Nr.
172 040 300
172 050 300
172 055 300

Reparatursätze



Ventile 6 Stück



Dichtsätze für 3 Kolben



Öldichtungssatz



Plungerrohr-Kit für 3 Kolben

R+M Nr.
172 900 001
172 900 002
172 900 002

R+M Nr.
172 900 185
172 900 024
172 900 024

R+M Nr.
172 900 186
172 900 186
172 900 186

R+M Nr.
172 900 008
172 900 009
172 900 009

COMET Motorpumpen

Motorpumpenkombinationen*




400 V. Alle Ausführungen mit Umlaufventil **, verzögerter Totalstopp-Steuerung, Druckmanometer, Elektrokabel 6 m und Ein-/Ausschalter. ☒ 3/4" AG ☑ M22 AG. Max. 30 °C

P	Q	U	KW	TYP
150	15	1.450	4,0	FW2 4025 TS+VA
210	15	1.450	5,5	FW2 4030 TS+VA
160	21	1.450	5,5	FW2 5523 TS+VA
170	15	1.450	4,5	RW 6.15 TS+VA

R+M Nr.
172 040 255
172 040 305
172 055 225
172 006 155

Reparatursätze




Ventile 6 Stück



Dichtsätze für 3 Kolben



Öldichtungssatz (7-teilig)



Plungerrohr für 3 Kolben

R+M Nr.
172 900 001
172 900 001
172 900 002
172 900 001

R+M Nr.
172 900 185
172 900 185
172 900 024
172 900 026

R+M Nr.
172 900 186
172 900 186
172 900 186
172 900 017

R+M Nr.	KØ
172 900 008	18
172 900 008	18
172 900 009	20
172 900 011	20

Heißwasserdichtsätze liefern wir auf Anfrage.

* mit Pumpe FW2 ab 2013
**Einstellung des Umlaufventils: Seite 65

Symbole P Druck Q Durchfluss U Umdrehungen KW Kilowatt TYP Typ KØ Kolbendurchmesser Spedition ☉ Gewinde I Höhe