

## Muffen reduziert

Innengewinde : Innengewinde



Messing

| IG : IG     | R+M Nr. | P       | I     |
|-------------|---------|---------|-------|
| 1/8" : 1/4" | 518 20  | 400 bar | 26 mm |
| 1/4" : 3/8" | 518 60  | 400 bar | 28 mm |
| 1/4" : 1/2" |         |         |       |
| 3/8" : 1/2" |         |         |       |



Edelstahl

| IG : IG | R+M Nr.     | P       | I     |
|---------|-------------|---------|-------|
|         | 040 001 023 | 400 bar | 26 mm |
|         |             |         |       |
|         |             |         |       |



Messing vernickelt

| IG : IG | R+M Nr. | P      | I     |
|---------|---------|--------|-------|
|         | 518 524 | 50 bar | 24 mm |
|         | 518 534 | 50 bar | 26 mm |
|         |         |        |       |
|         |         |        |       |

## Muffen

Innengewinde : Innengewinde



Sechskant. Messing

| IG : IG     | R+M Nr. | P       | I     |
|-------------|---------|---------|-------|
| 1/8" : 1/8" | 518 10  | 400 bar | 22 mm |
| 1/4" : 1/4" | 518 30  | 400 bar | 26 mm |
| 3/8" : 3/8" | 518 40  | 300 bar | 26 mm |
| 1/2" : 1/2" | 518 50  | 250 bar | 30 mm |
| 3/4" : 3/4" | 518 55  | 150 bar | 36 mm |



Sechskant. Edelstahl

| IG : IG | R+M Nr. | P       | I     |
|---------|---------|---------|-------|
|         | 518 19  | 500 bar | 22 mm |
|         | 518 39  | 500 bar | 25 mm |
|         | 518 49  | 400 bar | 26 mm |
|         | 518 59  | 400 bar | 34 mm |
|         | 518 559 | 250 bar | 36 mm |



Sechskant. Stahl verzinkt

| IG : IG     | R+M Nr. | P       | I     |
|-------------|---------|---------|-------|
| 1/4" : 1/4" | 518 32  | 400 bar | 25 mm |



Rund. Edelstahl

| IG : IG | R+M Nr. | P       | I     |
|---------|---------|---------|-------|
|         | 519 009 | 500 bar | 25 mm |

## Doppelnippel reduziert

Außengewinde : Außengewinde



Messing

| AG : AG     | R+M Nr. | P       | I     |
|-------------|---------|---------|-------|
| 1/8" : 1/4" | 570 20  | 400 bar | 22 mm |
| 1/8" : 3/8" | 570 30  | 400 bar | 23 mm |
| 1/4" : 3/8" | 570 50  | 400 bar | 24 mm |
| 1/4" : 1/2" | 570 60  | 400 bar | 27 mm |
| 3/8" : 1/2" | 570 80  | 400 bar | 27 mm |
| 3/8" : 3/4" |         |         |       |
| 1/2" : 3/4" | 571 00  | 250 bar | 34 mm |
| 3/4" : 1"   | 571 20  | 150 bar | 38 mm |



Edelstahl

| AG : AG | R+M Nr. | P       | I     |
|---------|---------|---------|-------|
|         | 570 29  | 500 bar | 29 mm |
|         | 570 39  | 500 bar | 30 mm |
|         | 570 59  | 500 bar | 33 mm |
|         | 570 69  | 500 bar | 37 mm |
|         | 570 89  | 500 bar | 40 mm |
|         |         |         |       |
|         | 571 09  | 400 bar | 43 mm |
|         | 571 29  | 250 bar | 45 mm |



Stahl verzinkt

| AG : AG | R+M Nr. | P       | I     |
|---------|---------|---------|-------|
|         | 570 28  | 500 bar | 28 mm |
|         | 570 38  | 500 bar | 30 mm |
|         | 570 58  | 500 bar | 32 mm |
|         | 570 68  | 500 bar | 35 mm |
|         | 570 88  | 500 bar | 37 mm |
|         | 570 858 | 400 bar | 39 mm |
|         | 571 08  | 400 bar | 40 mm |
|         | 571 28  | 250 bar | 46 mm |

Symbole IG Innengewinde AG Außengewinde I Höhe P Druck