

Lösbare Verschraubungen

Außengewinde : Außengewinde



Edelstahl

AG : AG
1/2" : 1/2"
3/4" : 3/4"

R+M Nr.	P	↑
574 812 009	max. 150 bar	67
574 834 009	max. 150 bar	73

Handverschraubungen ST-740 und Stecknippel ST-741

Handverschraubungen ST-740 und Stecknippel ST-741



HV M24 : AG.
Max. 700 bar / 150 °C



HV M24 : AG.
Max. 700 bar / 150 °C



AG : M24 AG.
Max. 700 bar / 150 °C



M24 AG : M24 AG.
Max. 700 bar / 150 °C

⊙
1/4"
3/8"
1/2"
M24

R+M Nr.
200 740 501
200 740 503

R+M Nr.
200 740 601

R+M Nr.
200 741 505
200 741 501
200 741 503

R+M Nr.
200 741 600



HV M24 : IG.
Max. 700 bar / 150 °C



HV M24 : IG.
Max. 700 bar / 150 °C



IG : M24 AG.
Max. 700 bar / 150 °C

⊙
1/4"
3/8"
M16x1

R+M Nr.
200 740 504
200 740 502
200 740 506

R+M Nr.
200 740 604
200 740 602

R+M Nr.
200 741 504
200 741 502

Dichtungen



O-Ring - ST-740

R+M Nr.
050 000 408



O-Ring - ST-741

R+M Nr.
050 001 000



Stützring - ST-740

R+M Nr.
050 000 407

Symbole IG Innengewinde AG Außengewinde ↔ Länge ↑ Höhe ⊙ Gewinde ⊗ Durchmesser TYP Typ P Druck