

## Suttner Drehverschraubungen ST-44 (Swivel)

## Handverschraubungen : Außengewinde



HV M22 : AG. Max. 400 bar / 150 °C

K



HV M21 : AG. Max. 400 bar / 150 °C

W



HV M22 : AG. Max. 200 bar

⊙	
1/4"	
3/8"	
1/2"	
M18	
M22	

R+M Nr.	ⓘ
568 00	49 mm
568 25	70 mm
568 26	73 mm
568 30	76 mm
568 10	76 mm

R+M Nr.	ⓘ
568 50	49 mm
568 70	46 mm

R+M Nr.	ⓘ
200 044 510	49 mm

HV M22 : M22 AG. Edelstahl.  
Max. 400 bar / 150 °C

K

⊙	
M22	

R+M Nr.	ⓘ
568 19	56 mm

## Handverschraubungen : Innengewinde



HV M22 : IG. Max. 400 bar / 150 °C

K



HV M22 : IG. Max. 400 bar / 150 °C

K



HV M21 : IG. Max. 400 bar / 150 °C

W

⊙	
1/4"	
3/8"	

R+M Nr.	ⓘ
568 15	67 mm

R+M Nr.	ⓘ
568 20	68 mm

R+M Nr.	ⓘ
568 80	67 mm

## Dichtungen ST-44



O-Ring



Nutting



O-Ring (hinten)



Stützring



Dichtsatz

R+M Nr.	VPE
050 000 651	1
568 009 100	100

R+M Nr.	
050 000 379	

R+M Nr.	TYP
568 011	klein
568 010	groß

R+M Nr.	VPE
050 001 511	1
568 008 100	100

R+M Nr.	
568 001 1	

Symbole ⓘ Höhe ⊙ Gewinde VPE Verpackungseinheit TYP Typ