

Handverschraubungen passend für System 2000




HV M22 : AG. Max. 400 bar / 150 °C

K

☉	1/4"
---	------

R+M Nr.	☐
560 302	30 mm



HV M22 : IG. Max. 400 bar / 150 °C

K

R+M Nr.	☐
561 302	45 mm



HV M22 : AG. Max. 400 bar / 150 °C

K

R+M Nr.	☐
561 402	49 mm



HV M22 : IG. Max. 400 bar / 150 °C

K

☉	3/8"
---	------

R+M Nr.	☐
561 502	47 mm



HV M22 : AG. Max. 400 bar / 150 °C

K

R+M Nr.	☐
561 602	50 mm

Handverschraubungen US


Handverschraubungen US



HV M22 : IG.
Max. 400 bar / 150 °C

☉	3/8" IG
---	---------

R+M Nr.	☐
561 501	45 mm



M22 : IG.
Max. 400 bar / 150 °C


R+M Nr.	☐
565 402	29



HV M22 : AG.
Max. 400 bar / 150 °C

☉	1/4" AG
	3/8" AG

R+M Nr.	☐
561 601	46 mm



M22 : AG.
Max. 400 bar / 150 °C

R+M Nr.	☐
565 302	29

Ersatzdichtung



O-Ring. Handverschraubung US.
10,77 x 2,62. NBR 70

R+M Nr.	☐	VPE
903 825 00	1	
790 117 726 210 0	100	

Symbole ☐ Höhe ☉ Gewinde TYP Typ