







## Höchstdruckschläuche






Schläuche mit zwei Drahteinlagen und gewickelter Decke. Typ 2SC. DN 10. 3,5-fache Sicherheit. Edelstahl Armaturen. Max. 150 °C

Dichtkegel (DKOS)		AGR : AGR		Handverschraubung	
M22 : M22		3/8" : 3/8"		M22 : M22	
					
maxpressure. Typ 2SC. Max. 500 bar	Typ 2SC. Max. 500 bar	maxpressure. Typ 2SC. Max. 500 bar	Typ 2SC. Max. 500 bar	maxpressure. Typ 2SC. Max. 500 bar	Typ 2SC. Max. 500 bar
<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 
358 177 310 9 10 m	364 177 310 9 10 m	358 144 310 9 10 m	364 144 310 9 10 m	358 100 310 9 10 m	364 100 310 9 10 m
358 177 315 9 15 m	364 177 315 9 15 m	358 144 315 9 15 m	364 144 315 9 15 m	358 100 315 9 15 m	364 100 315 9 15 m
358 177 320 9 20 m	364 177 320 9 20 m	358 144 320 9 20 m	364 144 320 9 20 m	358 100 320 9 20 m	364 100 320 9 20 m
358 177 330 9 30 m	364 177 330 9 30 m	358 144 330 9 30 m	364 144 330 9 30 m	358 100 330 9 30 m	364 100 330 9 30 m





Schläuche mit zwei Drahteinlagen und gewickelter Decke. DN 10. Edelstahl Armaturen. Max. 150 °C

Handverschraubung		
M24 : M24		
		
maxpressure. 2SC. Max. 500 bar	2SC. Max. 500 bar	2SN. Max. 600 bar
<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 
358 197 310 9 10 m	364 197 310 9 10 m	368 697 610 9 10 m
358 197 315 9 15 m	364 197 315 9 15 m	368 697 615 9 15 m
358 197 320 9 20 m	364 197 320 9 20 m	368 697 620 9 20 m
358 197 330 9 30 m	364 197 330 9 30 m	368 697 630 9 30 m

Schläuche mit zwei Drahteinlagen und gewickelter Decke. DN 10. Edelstahl Armaturen. Max. 150 °C

Handverschraubung : AG	
M24 : M24	
	
maxpressure. 2SC. Max. 500 bar	2SC. Max. 500 bar
<b>R+M Nr.</b> 	<b>R+M Nr.</b> 
358 114 431 09 10 m	364 114 471 09 10 m
358 114 431 59 15 m	364 114 471 59 15 m
358 114 432 09 20 m	364 114 472 09 20 m
358 114 433 09 30 m	364 114 473 09 30 m
<b>R+M Nr.</b> 	

Schläuche mit zwei Drahteinlagen und glatter Decke. DN 6. Edelstahl Armaturen. Max. 150 °C

Handverschraubung / AGR		
M22 : M22	M22 : 1/8"	1/4" : 1/4"
		
flexy 500. Max. 500 bar	flexy 500. Max. 500 bar	flexy 500. Max. 500 bar
<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 
338 000 310 9 10 m	424 300 010 9 10 m	424 344 010 9 10 m
338 000 315 9 15 m	424 300 015 9 15 m	424 344 015 9 15 m
338 000 320 9 20 m	424 300 020 9 20 m	424 344 020 9 20 m
338 000 330 9 30 m	424 300 030 9 30 m	424 344 030 9 30 m