

Suttner Strömungswächter

ST-505 Strömungswächter 600 bar



Schwimmer ST-505 mit Bohrung



R+M Nr.
200 005 301

R+M Nr.	Kabel
200 005 435	1.200 mm
200 005 438	3.500 mm

Schwimmer VA mit Bohrung.
Kontakt 1 A - 250 V.

R+M Nr.	Einbau	ein/aus	°C	↔	Kabel
200 505 706	3/8" IG senkrecht	3,3/1,8	80	30 l/min	1.200 mm
200 505 709	3/8" IG senkrecht	2,9/1,7	80	30 l/min	3.500 mm



Schwimmer ST-505 ohne Bohrung



R+M Nr.
200 005 526

R+M Nr.	Kabel
200 005 435	1.200 mm
200 005 438	3.500 mm

Schwimmer Messing ohne Bohrung.
Kontakt 1 A - 250 V.

R+M Nr.	Einbau	ein/aus	°C	↔	Kabel
200 505 708	3/8" IG senkrecht	0,5/0,1	80	30 l/min	1.200 mm
200 505 711	3/8" IG senkrecht	0,5/0,1	80	30 l/min	3.500 mm



Schwimmer ST-505 ohne Bohrung



R+M Nr.
200 005 311

REED-Schalter

R+M Nr.
200 005 438

Schwimmer VA ohne Bohrung. Kontakt 1 A - 250 V

R+M Nr.	Einbau	ein/aus	°C	↔	Kabel
205 505 707	3/8" IG senkrecht	1,8/1,3	80	30 l/min	1.200 mm