

Verschraubungen für Schneidringssystem

Einschraubverschraubungen



X-GE. Stahl verzinkt

R+M Nr.	TYP	AG	AG	I
580 90	6 LL	M10	1/8"	20
580 95	6 L	M12	1/8"	23
580 98	6 L	M12	1/4"	28
580 99	8 L	M14	1/8"	24
581 00	8 L	M14	1/4"	29
581 05	8 L	M14	3/8"	31
581 10	10 L	M16	1/4"	30
581 20	10 L	M16	3/8"	28
581 25	10 L	M16	1/2"	34
581 50	12 L	M18	1/4"	31
581 60	12 L	M18	3/8"	28
581 55	12 L	M18	1/2"	31
581 141 21	14 S	M22	1/2"	41



X-GE. Edelstahl

R+M Nr.	TYP	AG	AG	I
581 19	10 L	M16	1/4"	30
581 29	10 L	M16	3/8"	28
581 59	12 L	M18	1/4"	31
581 69	12 L	M18	3/8"	28
596 143 81	14 S	M22	3/8"	39
596 141 21	14 S	M22	1/2"	41

Aufschraubverschraubungen



X-GAI. Stahl verzinkt

R+M Nr.	TYP	IG	AG	I
580 00	6 L	1/4"	M12	25
580 10	8 L	1/4"	M14	31
580 20	10 L	1/4"	M16	32
580 50	10 L	3/8"	M16	28
580 30	12 L	1/4"	M18	33
580 40	12 L	3/8"	M18	33



X-GAI. Edelstahl

R+M Nr.	TYP	IG	AG	I
580 29	10 L	1/4"	M16	32
580 39	12 L	1/4"	M18	33

Nominal Druck nach DIN 2401

LL = sehr leichte Baureihe

L = leichte Baureihe

S = schwere Baureihe

Andere Verschraubungen liefern wir auf Anfrage.

TYP	Edelstahl	Verzinkt
LL ( 4 - 8)	100 bar	100 bar
L ( 6 - 10)	315 bar	500 bar
L (12 - 18)	315 bar	100-400 bar
L (22 - 42)	160 bar	250 bar
S ( 6 - 10)	630 bar	800 bar
S (12 - 16)	490 bar	630 bar
S (20 - 38)	315 bar	420 bar

Doppelnippel / Verbinder



X-G. Stahl verzinkt

R+M Nr.	TYP	AG	I
581 30	10 L	M16	27
581 70	12 L	M18	28



X-G. Edelstahl

R+M Nr.	TYP	AG	I
581 79	12 L	M18	28

Winkelverschraubungen



WE-R-keg. Stahl verzinkt.  
Mit Ü-Mutter + Schneidring

R+M Nr.	TYP	AG	Ø	↔
583 00	6 L	1/8"	6	28
583 20	12 L	3/8"	12	35
583 121 4	12 L	1/4"	12	35

Rohrstutzen



EG. Stahl verzinkt.  
Mutter + Schneidring vormontiert

R+M Nr.	TYP	Ø	AG	Ø	I
581 12	8 L	M14	1/4"	8	42
581 11	10 L	M16	1/4"	10	40
581 138 2	10 L	M16	3/8"	10	44
581 61	12 L	M18	3/8"	12	47
581 619*	12 L	M18	3/8"	12	47
581 13	12 L	M18	1/4"	12	47



X-EG. Stahl verzinkt.  
Ohne Mutter + Schneidring

R+M Nr.	Ø	AG	Ø	I
582 25	M18	3/8"	12	47

Schneidring



Stahl verzinkt

R+M Nr.	TYP	Ø
584 102	L / S	10
584 122	L / S	12

Ü-Mutter



Stahl verzinkt

R+M Nr.	TYP	Ø
584 101	10 L	M16
584 121	12 L	M18

\* Edelstahl

Symbole IG Innengewinde AG Außengewinde Ø Durchmesser ↻ Eingang ↺ Ausgang P Druck