

## Handverschraubungen ST-740 und Stecknippel ST-741

### Handverschraubungen ST-740 und Stecknippel ST-741



HV M24 : AG.  
Max. 700 bar / 150 °C



HV M24 : AG.  
Max. 700 bar / 150 °C



AG : M24 AG.  
Max. 700 bar / 150 °C



M24 AG : M24 AG.  
Max. 700 bar / 150 °C

⊙
3/8"
1/2"
M24

<b>R+M Nr.</b>
200 740 501
200 740 503

<b>R+M Nr.</b>
200 740 601

<b>R+M Nr.</b>
200 741 501
200 741 503

<b>R+M Nr.</b>
200 741 600



HV M24 : IG.  
Max. 700 bar / 150 °C



HV M24 : IG.  
Max. 700 bar / 150 °C



IG : M24 AG.  
Max. 700 bar / 150 °C

⊙
1/4"
3/8"

<b>R+M Nr.</b>
200 740 504
200 740 502

<b>R+M Nr.</b>
200 740 604
200 740 602

<b>R+M Nr.</b>
200 741 504
200 741 502

### Dichtungen



O-Ring - ST-740

<b>R+M Nr.</b>
050 000 408



O-Ring - ST-741

<b>R+M Nr.</b>
050 001 000



Stützring - ST-740

<b>R+M Nr.</b>
050 000 407