


Handverschraubungen passend für System 2000



HV M22 : AG. Max. 400 bar / 150 °C

	R+M Nr.
1/4"	560 302 30 mm



HV M22 : IG. Max. 400 bar / 150 °C

	R+M Nr.
	561 302 45 mm



HV M22 : AG. Max. 400 bar / 150 °C

	R+M Nr.
	561 402 49 mm



HV M22 : IG. Max. 400 bar / 150 °C

	R+M Nr.
3/8"	561 502 47 mm



HV M22 : AG. Max. 400 bar / 150 °C

	R+M Nr.
	561 602 50 mm

Handverschraubungen US

Handverschraubungen US



HV M22 : IG.
Max. 400 bar / 150 °C

	R+M Nr.
3/8" IG	561 501 45 mm



M22 : IG.
Max. 400 bar / 150 °C

	R+M Nr.
	565 402 29



HV M22 : AG.
Max. 400 bar / 150 °C

	R+M Nr.
1/4" AG	
3/8" AG	561 601 46 mm



M22 : AG.
Max. 400 bar / 150 °C

	R+M Nr.
	565 302 29

Ersatzdichtung



O-Ring. Handverschraubung US.
10,77 x 2,62. NBR 70

	R+M Nr.
	903 825 00

Symbole Höhe Gewinde