

## Umlaufventile


VB350



☉ = Eingang 3/8" AG. ☉ = Ausgang 3/8" IG.  
 BP = Bypass 1/2" IG. MN = Manometer 1/4" IG.  
 Umlaufventil mit Druckschalter (IP55) und Kabel  
 1.200 mm. Max. 350 bar / 90 °C

R+M Nr.	☐
532 350	40 l/min

VB350



☉ = Eingang 3/8" AG. ☉ = Ausgang 3/8" IG.  
 BP = Bypass 1/2" IG.  
 MN = Manometer 1/4" IG.  
 Max. 350 bar / 90 °C

R+M Nr.	☐
532 340	40 l/min

VB60/600



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG.  
 BP = Bypass 1/2" IG.  
 Max. 600 bar / 90 °C

R+M Nr.	☐
532 260 0	60 l/min

VB60/600



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG.  
 BP = Bypass 1/2" IG. Umlaufventil mit  
 Mikroschalter (IP55) und Kabel 950 mm.  
 Max. 600 bar / 90 °C

R+M Nr.	☐
532 265 0	60 l/min

Zeromatic 93



☉ = Eingang 1/2" IG. ☉ = Ausgang 3/8" AG.  
 BP = Bypass 1/2" IG. MN = Manometer 1/4" IG.  
 Max. 250 bar / 60 °C

R+M Nr.	☐
170 290 7	40 l/min