

Suttner Hochdruckschnellkupplungen ST-45-250 KW

Kupplungen und Stecknippel ST-45-250 KW



Kupplung : AG.
Edelstahl.
Max. 250 bar / 150 °C



Kupplung : IG.
Edelstahl.
Max. 250 bar / 150 °C



Kupplung : IG.
Edelstahl.
Max. 250 bar / 150 °C



Stecknippel : IG.
Edelstahl gehärtet.
Max. 250 bar / 150 °C

○	DN
1/4"	10
3/8"	10
1/2"	10
M22	10

R+M Nr.	⌈
200 045 595	49 mm

R+M Nr.	⌈
200 045 570	41 mm
200 045 560	41 mm
200 045 550	41 mm
200 045 575	41 mm

R+M Nr.	⌈
200 045 565	43 mm
200 045 555	43 mm

R+M Nr.	⌈
040 005 482	38 mm



Stecknippel : AG.
Edelstahl ungehärtet.
Max. 250 bar / 150 °C



Stecknippel : AG.
Edelstahl gehärtet.
Max. 250 bar / 150 °C



Kupplung : IG.
Messing vernickelt.
Max. 250 bar / 150 °C



Kupplung : IG.
Messing vernickelt.
Max. 250 bar / 150 °C

○	DN
1/4"	10
3/8"	10
1/2"	10

R+M Nr.	⌈
557 206	44 mm

R+M Nr.	⌈
040 005 669	42 mm

R+M Nr.	⌈
200 045 510	41 mm


R+M Nr.	⌈
200 045 505	43 mm




Stecknippel : IG.
Stahl verzinkt.
Max. 250 bar / 150 °C



Stecknippel : IG.
Edelstahl.
Max. 250 bar / 150 °C



O-Ring. 20x2,5. EPDM



O-Ring. 18x2,5. EPDM

○	DN
3/8"	10
1/2"	10

R+M Nr.	⌈
557 204	38 mm


R+M Nr.	⌈
557 209	38 mm
557 29	45 mm

R+M Nr.	VPE
792 025 100	100

R+M Nr.	VPE
791 825 100	100



Stecknippel : IG.
Stahl verzinkt + Messing.
Max. 250 bar / 150 °C



Kupplung : AG. Messing
vernickelt + Messing.
Max. 250 bar / 150 °C

○	DN
M22	10

R+M Nr.	⌈
557 205	73 mm

R+M Nr.	⌈
557 105	63 mm

000

Dichtsatz

R+M Nr.	M
557 104 11	EPDM
200 045 460	FKM