

## R+M EcoLine No. ONE

### R+M EcoLine No. ONE



Professionelle Pistole R+M EcoLine No. ONE.  
Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 500	1/4" IG	3/8" IG



Professionelle Pistole R+M EcoLine No. ONE.  
Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 550	1/4" IG	M22 AG



Professionelle Pistole R+M EcoLine No. ONE.  
Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 580	M22 AG	M22 AG



Professionelle Pistole R+M EcoLine No. ONE.  
Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 590	M22 AG	10 mm



Professionelle Pistole R+M EcoLine No. ONE.  
Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 591	M22 AG	11 mm



Professionelle Pistole R+M EcoLine No. ONE mit  
Kupplung KW. Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 560	Kupplung KW	3/8" IG
507 001 562	Kupplung KW	M22 AG

## R+M EcoLine No. ONE . Modernes Design - Innovativ - Zuverlässig

### R+M EcoLine No. ONE



Professionelle Pistole R+M EcoLine No. ONE mit Strahlrohr 900 mm Stahl verzinkt, Isolierung ST-28 Cool & Compact 300 mm und Düsenschutz ST-10 ohne Düse. Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 790	1/4" IG NPT	3/8" IG

### Ventil komplett



<b>R+M Nr.</b>
202 000 044

### Kolbenstange



<b>R+M Nr.</b>
201 000 900

### ST-300 Drehgelenke



3/8" AG : 3/8" IG

<b>R+M Nr.</b>
200 300 010



Professionelle Pistole R+M EcoLine No. ONE mit Strahlrohr 900 mm Stahl verzinkt, Isolierung ST-28 Cool & Compact 300 mm und Düsenschutz ohne Mundstück. Max. 250 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
507 001 951	Düsenschutz	M22 AG



Reparaturset ST-300

<b>R+M Nr.</b>
200 300 100