


Automatik Hochdruckschlauchaufroller

SoST 14 / SoST 20




| TYP | Außen \varnothing = Schlauch |
|-----|--------------------------------|
| 01 | 15,0 mm = 14 m |
| 02 | 15,0 mm = 20 m |

Stahl pulverbeschichtet. Einsatz in trockener Umgebung

| R+M Nr. | ★ | Ⓒ | Ⓔ | DN | P | °C | Ⓔ | 1 | 2 | 3 | 4 | TYP |
|---------|---|---------|---------|----|---------|-------|---------|--------|--------|--------|--------|-----|
| 740 002 | ● | 3/8" IG | 1/2" IG | 10 | 400 bar | 90 °C | 14,0 kg | 470 mm | 470 mm | 107 mm | 135 mm | 01 |
| 740 005 | ● | 3/8" IG | 1/2" IG | 10 | 400 bar | 90 °C | 16,0 kg | 470 mm | 470 mm | 167 mm | 195 mm | 02 |

SoST 14 / SoST 20



| TYP | Außen \varnothing = Schlauch |
|-----|--------------------------------|
| 01 | 15,0 mm = 14 m |
| 02 | 15,0 mm = 20 m |

Edelstahl V2A / AISI 304. Einsatz in nasser Umgebung

| R+M Nr. | ★ | Ⓒ | Ⓔ | DN | P | °C | Ⓔ | 1 | 2 | 3 | 4 | TYP |
|---------|---|---------|---------|----|---------|-------|---------|--------|--------|--------|--------|-----|
| 740 008 | ● | 3/8" IG | 1/2" IG | 10 | 400 bar | 90 °C | 14,0 kg | 470 mm | 470 mm | 107 mm | 135 mm | 01 |
| 740 009 | ● | 3/8" IG | 1/2" IG | 10 | 400 bar | 90 °C | 16,0 kg | 470 mm | 470 mm | 167 mm | 195 mm | 02 |