


Handverschraubungen passend für System 2000



HV M22 : AG. Max. 400 bar / 150 °C

K



HV M22 : IG. Max. 400 bar / 150 °C

K



HV M22 : AG. Max. 400 bar / 150 °C

K

	1/4"
--	------

R+M Nr.	
560 302	30 mm

R+M Nr.	
561 302	45 mm

R+M Nr.	
561 402	49 mm



HV M22 : IG. Max. 400 bar / 150 °C

K



HV M22 : AG. Max. 400 bar / 150 °C

K

	3/8"
--	------

R+M Nr.	
561 502	47 mm


R+M Nr.	
561 602	50 mm

Handverschraubungen US

Handverschraubungen US



HV M22 : IG.
Max. 400 bar / 150 °C



M22 : IG.
Max. 400 bar / 150 °C

Ersatzdichtung



O-Ring. Handverschraubung US.
10,77 x 2,62. NBR 70

	3/8" IG
--	---------


R+M Nr.	
561 501	45 mm

R+M Nr.	
565 402	29

R+M Nr.	
903 825 00	1
790 117 726 210 0	100



HV M22 : AG.
Max. 400 bar / 150 °C



M22 : AG.
Max. 400 bar / 150 °C

	1/4" AG
	3/8" AG

R+M Nr.	
561 601	46 mm

R+M Nr.	
565 302	29

Symbole Höhe Gewinde Typ