

## Suttner Hochdruckspritzpistolen

## ST-1500



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 500	1/4" IG	3/8" IG



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 560	1/4" IG	3/8" IG dreh.





Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 550	1/4" IG	M22 AG





Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 545	M22 AG	M22 AG



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 760	HV M22	M22 AG



Professionelle Pistole. Frostschutzausführung.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 580	1/4" IG	3/8" IG



Professionelle Pistole. Frostschutzausführung.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 581	1/4" IG	3/8" IG dreh.



Professionelle Pistole. Weepausführung.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 620	1/4" IG	3/8" IG



Professionelle Pistole ohne Ventil (Freifluss).  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 750	1/4" IG	3/8" IG

## ST-300 Drehgelenk



1/4" IG : 3/8" IG. ST-1500

R+M Nr.
200 300 050



Reparatursatz ST-300

R+M Nr.
200 300 100

## Reparatursatz



ST-1100. Drehgelenk

R+M Nr.
200 300 100

## Dichtsatz



ST-1100

R+M Nr.
201 100 401

## Ventile komplett



ST-1500

R+M Nr.
202 000 044



ST-1500 Weep

R+M Nr.
202 000 045



ST-1500 Frostschutz

R+M Nr.
202 000 101

Symbole  Ausgang  Eingang